

Zerust® Axxanol™ Spray-G

For superior corrosion protection in a sprayable grease, use Zerust®/Excor® Axxanol Spray-G. It protects in extreme conditions, such as during outdoor storage and overseas shipping.

Axxanol Spray-G provides the protection of a grease in the convenience of a sprayable form. It outperforms many other rust preventative coatings, while being easier to apply and remove, saving time and costs associated with corrosion control. The product has an oily grease consistency and provides advanced corrosion protection for parts and equipment for up to 1 year outdoors and 2 years indoors.

Axxanol Spray-G can be used as a light lubricant while it provides exceptional corrosion protection. The product is resistant to water and is compatible with packaging and most rubber and plastic materials. Test on a small area before use. Check with your Zerust/Excor representative for a corrosion management solution most effective for your metal assets.

Application Example

A large piece of machinery was coated with Axxanol Spray-G before shipment overseas. It was shipped on the deck and in extreme open-air conditions. The item arrived corrosion-free to the end customer.



Benefits

Sprayable multimetal rust preventative coating

Protects in extreme outdoor conditions

Safe for paint and plastic

Non-hazardous* disposal

Removable with an alkaline cleaner

Application Type

Storage
Shipping
During Operation
May be used with Zerust VCI packaging

*Non-Hazardous Disposal: Product in unopened original container prior to use is non-hazardous waste in the United States according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).



Technical Data

Product Information	Solvent-based corrosion inhibitor sprayable grease.	
Application	Apply via pressurized spray	
Tested on 1010 Steel panels with 20 Ra roughness	Application temperature	50 to 90°F (10 to 32°C)
	Coverage	211 ft ² (20 m ²) per lb 1900 ft ² (180 m ²) per gal
	Layer Thickness	1 mil (25 µm)
	Removability	Alkaline cleaner
	Max VOC content	40%
	Flash Point	177° F (80.5°C)
	Zahn Cup #3 Viscosity	13-20 secs @ 25°C
Protection Properties	Indoors	Up to 2 years
Tested at 2 mil (50 µm)	Outdoor	Up to 1 year
	ASTM D1748 Humidity	Meets or exceeds 1320 hrs
	ASTM B117 Salt Spray	Meets or exceeds 1500 hrs
	Packaging/Hermetically Sealed	Up to 5 years
	Metal types	Multimetal protection
Storage Guidelines	Temp	50 to 90°F (10 to 32°C)
	Duration	Up to 2 years

Availability

Zerust®/Excor® Axxanol™ Spray-G is sold in a ready-to-use aerosol can and in bulk pails and drums. Large volume pricing available upon request.

Part Number	Qty
350-M-00023AC	12 oz
350-M-00023PL	5 Gal*
350-M-00023DR	55 Gal*

*5 Gallon approx. 35 lbs, 55 Gallon approx. 400 lbs

Contact an Expert

Consult your local Zerust/Excor representative to implement an optimum corrosion prevention system for your production facility and supply chain.

Safety

- Product in unopened original container prior to use does not meet criteria for hazardous waste according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).

Warranty and Disclaimer Information: We guarantee our products conform to documented quality specifications. All statement, technical information and recommendations contained herein are based on testing and experiences NTIC believes to be reliable, but the accuracy or completeness thereof is not guaranteed. Product information subject to change without notice. We make no warranty of any kind expressed or implied as to the effects of use (including, but not limited to, damage or injury). For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2013-2017 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor-Tab®, EXCOR®, Flange Saver®, ICT®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, The ZERUST People®, and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

Contact Us



A product of:
Northern Technologies
International Corp
4201 Woodland Road
Circle Pines, MN 55014
USA

Phone. +1 763.225.6600
Fax. +1 763.225.6645
sales@zerust.com
www.zerust.com

